



OSB Information Sheet

Classification: Exposure 1 - OSB Suitable for uses not permanently exposed to the weather. Panels classified as Exposure 1 are intended to resist the effects of moisture on structural performance as may occur due to construction delays, or other conditions of similar severity.

Code Fire Classification: Class III or C

Flame Spread Rating: 76-200, smoke-developed index <450

Building Code Compliance: PS 2-18

PS 2 structural panel are exempt from testing by California Air Resources Board (CARB) in the Composite Wood Air Toxic Control Measure (ATCM) and phenolic bonded structural panels are exempt from testing or monitoring by HUD in the Manufacturing Home Construction and Safety Standards

Thickness	Application	Span Rating	Pack Size
23/32" Sanded Groove or Squared Edge	Single Layer Flooring	24" O.C.	47 Pieces
19/32" Sanded Groove or Squared Edge	Single Layer Flooring	20" O.C.	55 Pieces
5/8" Sheathing	Sub Floor	20" O.C.	55 Pieces
	Roof	40" O.C.	
1/2" Sheathing	Sub Floor	16" O.C.	65 Pieces
	Roof	32" O.C.	
	Wall	24" O.C.	
15/32" Sheathing	Sub Floor	16" O.C.	70 Pieces
	Roof	32" O.C.	
	Wall	24" O.C.	
7/16" Sheathing	Sub Floor	16" O.C.	75 Pieces
	Roof	24" O.C.	
	Wall	24" O.C.	
3/8" Sheathing	Wall	24" O.C.	85 Pieces